

BGC Fibre Cement Product Guide



bgcinnovadesign.com.au

History & Mission

BGC Services

BGC Fibre Cement is a proud Australian owned manufacturer of fibre cement products.

- / Split packs
- / Free estimations
- / Direct to site deliveries
- / Staff training
- / Dual calls

BGC has state-of-the-art manufacturing facilities in Perth and distribution centres in all states of Australia and in New Zealand.

Our distribution network ensures that our entire product range is readily available in all states of Australia and in New Zealand.

BGC has a team of technical specialists that can assist with all specification and design information to help ensure that you always **'build it better with BGC'**.

BGC HAS INTERESTS IN

- / Residential and commercial building
- / Building and construction products
- / Contract mining
- / Civil engineering construction and maintenance
- / Quarrying
- / Road transport
- / Property ownership and management
- / Insurance

Contents



Our mission at BGC is simple – we want to ensure that people can always **‘build it better with BGC’**.

In keeping with our mission, we are constantly assessing and improving our products to ensure that we always provide cost effective, high quality and easy-to-use products to the market.



- 6 // CASE STUDY RESIDENTIAL
- 7 // CASE STUDY COMMERCIAL

INNOVA™

- 8 // DURAGRID™
- 9 // DURACOM™
- 10 // DURACOM GREYSTONE™
- 11 // DURASCAPE™
- 12-13 // DURAGROOVE™
- 14-15 // STRATUM™
- 16 // STRATUM™ ERA
- 17 // NULLINE™ PLUS
- 18 // STONESHEET™
- 19 // DURAFLOOR™
- 21 // DURAGRID™ ACCESSORIES
- 21 // DURACOM™ ACCESSORIES
- 21 // DURAGROOVE™ ACCESSORIES
- 22 // STRATUM™ ACCESSORIES
- 22 // NULLINE™ PLUS ACCESSORIES

BGC FIBRE CEMENT

- 23 // DURASHEET™
- 24 // DURAPLANK™
- 25 // DUARTEX™
- 26 // DURALATTICE™
- 27 // DURALINER™ PLUS
- 28 // DURALUX™ PLUS
- 29 // COMPRESSED FLOORING
- 30 // CERAMIC TILE UNDERLAY
- 31 // VINYL AND CORK UNDERLAY
- 32 // TERMS AND CONDITIONS
- 32 // WARRANTY

Specify Fibre Cement facade systems with confidence

bgcinnovaldesign.com.au /fire-resistant





Innova™ deemed to comply external facade systems.

- / Compressed fibre cement range
- / Architectural designed weatherboard range
- / Grooved and profiled cladding range

BGC's products have superior fire performance against four key indices.



Ignition index = 0

Fibre cement does not ignite



Spread of flame index = 0

There is no spread of fire with fibre cement



Heat evolved index = 0

Heat does not evolve from fibre cement



Smoke developed index = 0-1

Smoke is not emitted from fibre cement



Up to **BAL 40**
as per AS3959:2009



Tested in Australia by accredited Australian authorities **CSIRO** and **Exova Warrington**

Case Study 01.

Residential

Project: 119 Gabriel
Location: Cloverdale, Western Australia
Architect: Modan
Developer: Modan
Products used: Duragrid™
Duragroove™ / Durascape™

119 Gabriel is an affordable housing development comprising of 5 townhouses located in Cloverdale, Western Australia. Designed using flexible apartment principles with a high quality finish, the Innova™ range offered a designer touch with robust and functional benefits.

“The advantages of using the Innova™ system is the architectural forms we could create. We used Duragrid™ and Duragroove™ to embellish the architectural features and create some differentiation in the facade. We have been really happy with the product from Innova™ and will certainly be using them again”.

Arun Broadhurst
Director, Modan



Case Study 02.

Commercial

Project: Westfield Shopping Centre
Location: Carousel, Western Australia
Architect: Scentre Group
Contractor: Denmac
Products used: Duracom™ / Duralux™

BGC supplied a variety of fibre cement products to the new extension to the Westfield Carousel Shopping Centre. Duracom™ was used by Denmac who were contracted to install the external cladding. Duralux™ was also used as soffit lining, which was installed by EXZO. BGC products allowed both Denmac and EXZO to achieve a robust finish without sacrificing design objectives.

“Duracom™ is backed by a well established company which means the product is always available when we need it, which minimised site laydown”.

Rob Innocent
Denmac





bgcinnovadesign.com.au/duragrid

The Duragrid™ facade system utilises BGC Fibre Cement sheeting, offering the ideal solution for cladding the exterior of low to medium rise homes. Duragrid™ gives buildings a modern and extremely durable finish.

Duragrid™ sheeting has a smooth, flat surface and square-edge finish that is suitable for expressed jointing and provides a facade suitable for a number of finishes; from painted to textured coatings.

- / Lightweight
- / Highly durable
- / Panels will not rot, burn or corrode
- / Panels are not affected by termites, air, steam, salt or sunlight
- / Can be easily decorated in a number of design finishes
- / Quick and simple to install using manual nailing, gun nailing or screw fixing

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm			
			1190	1790	2390	2990
9	13.5	590			✓	
		890		✓		
		1190	✓			✓

Accessories

PRODUCT	LENGTH mm	BGC CODE
Durabatten - Primed, graded timber	19 x 70 x 3000	491
	19 x 70 x 2700	490
Durabatten - Steel	35 x 70 x 3000	496
	19 x 70 x 3000	495
Horizontal Backing Strip	1190	839
	2390	841
	2990	843
Cavity Vent Strip - uPVC	19 x 2700	480
Sealant/Adhesive	Sikaflex 11FC or similar	485/486
Countersinker - Tungsten Carbide	Countersinking tool	855

bgcinnovadesign.com.au/duragrid
Some sizes may not be available in all states,
please check with your local BGC office for availability.



bgcinnovadesign.com.au/duracom

With its smooth, flat surface and square-edge finish, Duracom™ facade system is ideal for the exterior cladding of low to medium rise buildings. Utilising BGC's trusted fibre cement coated compressed sheeting, Duracom™ delivers a strikingly modern, durable finish.

Lightweight yet exceptionally resilient, Duracom™ facade system is perfect for expressed jointing and a variety of finishes; from painted to textured coatings.

- / Weather-resistant – simply shrugs off water. Rated for weatherability by CSIRO
- / Fully-sealed, balanced panels won't rot, burn or corrode
- / Allows easy decoration in a range of design finishes
- / Rapid installation
- / Complies with BAL40 as required in AS3959:2009 – construction of buildings in bushfire-prone areas

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm			
			1800	2400	2700	3000
6	9.8	1200		✓		✓
9	14.6	900	✓	✓		✓
		1200	✓	✓	✓	✓
12	19.5	1200		✓		✓

Accessories

PRODUCT	LENGTH mm	BGC CODE
Primary Top Hat - Galvanised Steel	120 x 35 x 1.15 BMT-6000	831
	120 x 35 x 1.15 BMT-7200	833
Intermediate Top Hat - Galvanised Steel	50 x 35 x 1.15 BMT-6000	835
	50 x 35 x 1.15 BMT-7200	837
Horizontal Backing Strip	1190	839
	2390	841
	2990	842
EPDM Foam Gasket	25000	845

bgcinnovadesign.com.au/duracom

Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnovadesign.com.au/greystone

Create that contemporary industrial look with Duracom Greystone™ from Innova™. With 2 shades to choose from, Natural and Charcoal, as well as 2 faces to choose from, Industrial and Velvet, you can create the perfect feature wall inside or out.

Duracom Greystone™ is a pre-finished panel that does not require painting or finishing on site. This reduces the need for painting trades and speeds up the building process. Duracom Greystone™ is ideal for use internally to create a striking feature wall or perfect for external use to create an eye catching facade.

- / Provides a modern industrial look with 2 different shades and 2 different faces
- / Lightweight and easy to install using a proven installation method
- / Great solution when panels may be difficult to maintain. The factory applied treatment means you do not need to recoat or repaint panels, reducing maintenance costs
- / Australian manufactured, tested and warranted
- / Panels are non-combustible, which ensures a perfect cladding option for both commercial and residential projects

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm	
			2400	3000
9	14.6	1200	✓	✓

Accessories

PRODUCT	LENGTH mm	BGC CODE
Primary Top Hat - Galvanised Steel	120 x 35 x 1.15 BMT-6000	831
	120 x 35 x 1.15 BMT-7200	833
Intermediate Top Hat - Galvanised Steel	50 x 35 x 1.15 BMT-6000	835
	50 x 35 x 1.15 BMT-7200	837
Horizontal Backing Strip BMT 0.42	1190	839
	2390	841
	2990	843
Duracom Greystone™ Weather Seal / Facade Washer		DCWSEAL
Duracom Greystone™ Edge Sealer		
EPDM Foam Gasket	25000	845

bgcinnovadesign.com.au/greystone
Some sizes may not be available in all states, please check with your local BGC office for availability.



Charcoal Industrial Charcoal Velvet



bgcinnovadesign.com.au/durascape

Durascape™ is a 9mm-thick base sheet. Excellent for covering large areas; its 5mm wide shiplap joint gives the sheet a subtle vertical shadow line.


To create an appealingly ‘rendered’ look, try finishing Durascape™ onsite with a roll-on textured paint.

- / Lightweight and durable
- / Ideal for single-storey and medium-height installations where you want large panels
- / Quick installation – no need for taped and filled joints
- / Panels unaffected by termites, air, steam, salt and sunlight
- / Can be finished in a range of decorative coatings

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm	
			2450	3000
9	13.5	900	✓	✓
		1200	✓	✓

Accessories

PRODUCT	LENGTH mm	BGC CODE
Internal Corner	3000	INTCNR12
External Corner	3000	EXTCNR12
Horizontal Flashing	3000	HORIZ9
EPDM Foam Gasket	25000	845



bgcinnovadesign.com.au/durascape
Some sizes may not be available in all states,
please check with your local BGC office for availability.



bgcinnovadesign.com.au/duragroove

For up-to-the-minute exteriors or interiors, choose Duragroove™ cladding. A peerlessly adaptable, vertically-grooved panel available in different profiles and spacing, Duragroove™ has a shiplap joint to ease and speed your installation.

Specify Duragroove™ for single-storey and medium-height projects. Duragroove™ comes in five variants:

- / Smooth Narrow 100mm
- / Smooth Wide 150mm
- / Smooth Extra Wide 400mm
- / Woodgrain Wide 150mm
- / Woodgrain Extra Wide 400mm

- / Vertical grooves – excitingly contemporary alternative to traditional weatherboard
- / Lightweight and durable
- / Factory sealed panels aid paint application
- / Quick to install – no need for taped and filled joints
- / Panels resistant to termites, air, steam, salt and sunlight



Smooth Narrow
100mm



Smooth Wide
150mm



Smooth Extra Wide
400mm



Woodgrain Wide
150mm



Woodgrain Extra Wide
400mm

bgcinnovadesign.com.au/duragroove
Some sizes may not be available in all states,
please check with your local BGC office for availability.



THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	PROFILE	LENGTH mm		
				2450	2750	3000
9	13.5	1200	Smooth Narrow	✓	✓	✓
			Smooth Wide	✓	✓	✓
			Smooth Extra Wide	✓	✓	✓
			Woodgrain Wide	✓	✓	✓
			Woodgrain Extra Wide	✓	✓	✓

Accessories

PRODUCT	LENGTH mm	BGC CODE
Internal Corner	3000	INTCNR12
External Corner	3000	EXTCNR12
External Snap On Corner - Part A	3600	SNAPCNRA36
External Snap On Corner - Part B	3600	SNAPCNRB36
Horizontal Flashing	3000	HORIZ9
EPDM Foam Gasket (used to prevent moisture ingress at sheet joins)	25000	845



A vibrant, innovative alternative to traditional weatherboards, Stratum™ is an endlessly adaptable range of plank products.

Choose one Stratum™ profile as a standalone, or mix'n'match two or three to create eye catching and original Innova™ exterior cladding.



Stratum™



Stratum™ Woodgrain



Stratum™ Duo



Stratum™ Duo Woodgrain



Stratum™ Trio



Stratum™ Contour

- / Stratum™ is a 300mm wide plank with a 16mm horizontal joint
- / Stratum™ Woodgrain is a 300mm wide weatherboard with a 16mm horizontal joint embossed with a woodgrain pattern giving a timber like appearance
- / Stratum™ Duo is a 300mm wide weatherboard with a 16mm centre groove and the look of two slimmer weatherboards
- / Stratum™ Duo Woodgrain is a 300mm wide weatherboard with a 16mm centre groove and the look of two slimmer weatherboards embossed with a woodgrain pattern giving a timber like appearance
- / Stratum™ Trio is a 300mm wide weatherboard with 2 x 16mm horizontal grooves
- / Stratum™ Contour is a 170mm wide weatherboard with a 2mm indentation at the top of each weatherboard
- / Easy shiplap joining
- / Factory sealed, ready for painting
- / Quick, simple installation: manual nailing, gun nailing or screw fixing

bgcinnovadesign.com.au/stratum

Some sizes may not be available in all states, please check with your local BGC office for availability.



THICKNESS mm	WEIGHT kg/lm	WIDTH mm	PROFILE	LENGTH mm	
				4200	2700
12	5.2	300	Stratum™	✓	✓
			Stratum™ Woodgrain	✓	✓
			Stratum™ Duo	✓	✓
			Stratum™ Duo Woodgrain	✓	✓
			Stratum™ Trio	✓	
10	2.5	170	Stratum™ Contour	✓	

Weights are based on Equilibrium Moisture Content

Accessories

PRODUCT	LENGTH mm	BGC CODE
Internal Corner - Stratum™ and Stratum™ Duo (may also be used for Stratum™ Contour)	3000 x 17	INTCNR17
External Corner - Stratum™ and Stratum™ Duo (may also be used for Stratum Contour)	3000 x 17	EXTCNR17
Internal Corner - Stratum™ Contour (recommended)	3000 x 36	INTCNR36
External Corner - Stratum™ Contour (recommended)	3000 x 36	EXTCNR36
External Snap on Corner - Part A	3600 x 45	SNAPCNR36
External Snap on Corner - Part B	3600 x 45	SNAPCNR36
Starter Strip - Stratum™ Contour	3000	680
EPDM Foam Gasket	25000	845
Sealant	Sika FC11 or similar	485



bgcinnovadesign.com.au/stratum-era

A vibrant, innovative alternative to traditional weatherboards, Stratum™ Era is a new addition to the popular Stratum™ range. Stratum™ Era complements the other products in the Stratum™ range.

Stratum™ Era is a 295mm wide plank designed to fix flat against the stud wall. 2 Horizontal features, 1 at the top and 1 in the centre give a unique look to Stratum™ Era that is traditional yet contemporary weatherboard.

- / Easy shiplap joining
- / Self aligning
- / Primed, ready for painting
- / Quick, simple installation: manual nailing, gun nailing or screw fixing

THICKNESS mm	WEIGHT kg/lm	WIDTH mm	LENGTH mm
10	4.1*	295	4200 ✓

*17.22KG per plank



Stratum™ Era

Accessories

PRODUCT	LENGTH mm	BGC CODE
Internal Corner	3000	INTCNR12
External Corner	3000	EXTCNR12
EPDM Foam Gasket	250000	845
Sealant	Sikaflex FC11 or similar	485

bgcinnovadesign.com.au/stratum-era
Some sizes may not be available in all states,
please check with your local BGC office for availability.



bgcinnovadesign.com.au/nuline-plus

Nuline™ Plus is a weatherboard-style cladding. With its perfect join and a seductive look that echoes real timber, Nuline™ Plus is the natural evolution of the ever-popular Nuline™ weatherboard.

The Nuline™ Plus tongue & groove fixing will deliver seamlessly consistent joins throughout your project. With its slight bevel on the rear of the plank allowing a 25mm bearing face on the stud, you'll find fixing and nailing exceptionally easy.

- / Extend your options with 2 different profiles: square and bullnose
- / Factory sealed, ready for painting
- / Quick, simple installation: manual nailing, Gun nailing or screw fixing
- / Highly durable: no rot or decay
- / Complies with BAL40 as required in AS3959:2009 construction of buildings in bushfire-prone areas

THICKNESS mm	WEIGHT kg/lm	WIDTH mm	LENGTH mm
			4200
14	3.5	175	✓
	4.2	205	✓

Accessories

PRODUCT	LENGTH mm	BGC CODE
Internal Corner	3000	INTCNR36
External Corner	3000	EXTCNR36
J Mould	2700	805
Starter Strip	2700	825



Square

Bullnose

bgcinnovadesign.com.au/nuline-plus
Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnovadesign.com.au/stonesheet

Stonesheet™ is your first call for a stone tile substrate and background for true masonry on timber or steel-framed buildings. A flat, square-edged sheet, Stonesheet™ comes as 9mm-thick panels.

Designed specially as a substrate for both residential interior and exterior applications, Stonesheet™ is an excellent alternative where other non-specifically designed substrates have been used.

- / Exterior and interior stone tile facades
- / Non-structural substrate
- / Classified type A category 3 for exterior use
- / Will take maximum stone facade weight of 40kg/m²

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm
9	13.2	1200	3000 ✓



bgcinnovadesign.com.au/stonesheet
Some sizes may not be available in all states,
please check with your local BGC office for availability.



bgcinnovadesign.com.au/durafloor


Your ultimate flooring solution, Durafloor™ is superb for interior wet areas such as bathrooms and laundries. You can also specify Durafloor™ for a variety of exterior uses.

Choose Durafloor™ for balconies, verandahs and sundecks. Alternatively, where premium quality is your main concern, insist on Durafloor™ as a total floor solution.

Use 19mm Durafloor™ where joist spacings are at 450mm centres. Durafloor™ 19mm has a pink tongue. Use 22mm Durafloor™ where joist spacings are at 600mm centres. Durafloor™ 22mm has a blue tongue.

- / Easy installation via traditional gun-nailing methods
- / Installation costs lower than standard compressed sheet
- / Same tongue & groove technology as traditional sheet flooring (eg: Structaflor®)
- / Greater impact resistance – feels more solid underfoot than timber-based sheet flooring products

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm		
			2250	2400	2700
19	26.2	600	✓		✓
22	31.5	600		✓	



Staggered Sheet Layout



Squared Sheet Layout







bgcinnovadesign.com.au/durafloor
Some sizes may not be available in all states, please check with your local BGC office for availability.

Innova™ Accessories







DURAGRID™

<p>Durabatten – Primed Timber 19mm x 70mm x 2700mm - 490 19mm x 70mm x 3000mm - 491</p> 	<p>Durabatten – Steel 19mm x 70mm x 3000 x 0.75 BMT - 495 35mm x 70mm x 3000 x 0.75 BMT - 496</p> 	<p>Horizontal Backing Strip 1190mm - 839, 2390mm - 841, 2990mm - 843</p> 
<p>Cavity Vent Strip – uPVC 19mm x 2700mm - 480</p> 	<p>Sealant Adhesive Sikaflex 11FC or Similar - 485</p> 	<p>Countersinking Tool Tungsten Carbide - 855</p> 

DURACOM™

<p>Primary Top Hat – Galvanised Steel 120mm x 35mm x 1.15 BMT-6000 - 831 120mm x 35mm x 1.15 BMT-7200 - 833</p> 	<p>Intermediate Top Hat– Galvanised Steel 50mm x 35mm x 1.15 BMT-6000 - 835 50mm x 35mm x 1.15 BMT-7200 - 837</p> 	<p>Horizontal Backing Strip 1190mm - 839, 2390mm - 841, 2990mm - 843</p> 
<p>EPDM Foam Seal 25m - 845</p> 		

DURASCAPE™ AND DURAGROOVE™

<p>External Corner 3000mm - EXTCNR12</p> 	<p>Internal Corner 3000mm - INTCNR12</p> 	<p>Horizontal Flashing 3000mm - HORIZ9</p> 
<p>External Snap on Corner - Part A 3600mm - SNAPCNR36</p> 	<p>External Snap on Corner - Part B 3600mm - SNAPCNRB36</p> 	<p>EPDM Foam Seal 25m - 845</p> 

STRATUM™

Internal Corner – Stratum™ Era
3000mm x 12mm profile - INTCNR12



Internal Corner – Stratum™ Duo and Trio
3000mm x 17mm profile - INTCNR17



Internal Corner – Stratum™ Contour
3000mm x 36mm profile - INTCNR36



External Corner – Stratum™ Era
3000mm x 12mm profile - EXTCNR12



External Corner – Stratum™ Duo and Trio
3000mm x 17mm profile - EXTCNR17



External Corner – Stratum™ Contour
3000mm x 36mm profile - EXTCNR36



External Snap on Corner - Part A
3600mm - SNAPCNRA36



External Snap on Corner - Part B
3600mm - SNAPCNRB36



Sealant Adhesive
Sikaflex 11FC or Similar - 485



Starter Strip
3000mm - 680



EPDM Foam Seal
25m - 845



NULINE™ PLUS

Internal Corner
3000mm x 36mm profile - INTCNR36



External Corner
3000mm - EXTCNR36



J Mould – Aluminium
2700mm - 805



External Snap on Corner - Part A
3600 - SNAPCNRA36



External Snap on Corner - Part B
3600 - SNAPCNRB36



Starter Strip – Zinalume
2700mm - 825





The BGC Innova™ Design website is home to all your technical data and installation needs.



Full range of facade linings and flooring



Case studies and testimonials



Download CAD, Revit, BIM, and 3D Jpeg

Go to our website for more information on the Innova™ range.
bgcinnovadesign.com.au

Contact us to find out more
Telephone 1300 652 242



bgcinnovadesign.com.au/durasheet

Durasheet™ provides first-rate external cladding for gable ends, eaves, soffits, carports and verandah linings. It's a general-purpose sheet you can use on both timber and steel-framed buildings.

Durasheet™ comes in two thicknesses to suit both residential and light commercial fibre cement applications, significantly extending your professional specifying choice.

- / 4.5mm thickness: used mainly in timber-framed residential buildings for soffit/eaves linings and cladding features such as gable ends
- / 6mm thickness: recommended for residential and light commercial applications, cyclonic wind zones and steel-framed constructions
- / Classified as Type A Category 2 for exterior use

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm				
			1800	2100	2400	2700	3000
4.5	6.6	450			✓		
		600			✓		
		750			✓		
		900	✓		✓	✓	✓
		1200	✓	✓	✓	✓	✓
6	8.8	900			✓	✓	✓
		1200	✓		✓	✓	✓



bgcinnovadesign.com.au/durasheet
Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnovadesign.com.au/duraplank

In its appealing look and easy installation, the design of Duraplank™ evokes traditional weatherboards. Duraplank™ won't decay, rot or become damaged by white ants, and it's non-combustible.

Beautifully attractive – you have the option of a smooth finish, a woodgrain or a rustic texture for an authentic weatherboard look – Duraplank™ also has the strength to withstand the rigours of family life.

- / Similar flavour to traditional weatherboards
- / No decay, rot or white ant damage
- / Safe and durable – needs only minimum maintenance
- / Variety of finishes
- / Complies with BAL29 as required in AS3959:2009 – Construction of buildings in bushfire-prone areas

THICKNESS mm	WEIGHT kg l/m	WIDTH mm	PROFILE	LENGTH mm
7.5	2.2	205	Rusticated	4200
	2.5	230	Smooth & Woodgrain	
	3.3	300	Smooth & Woodgrain	

bgcinnovadesign.com.au/duraplank

Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnovaldesign.com.au/duratex

A tough, durable, waterproof external cladding system, Duratex™ provides a solid substrate for applied decorative finishes when combined with proprietary jointing and coating systems.

Tough, durable, waterproof and fire-resistant, Duratex™ is great for lightweight construction and features a factory-applied blue tint to help with identification.

- / Specify for residential and commercial applications
- / Accepts a wide range of textured coatings
- / Complies with AS3959:2009 – Construction of buildings in bushfire-prone areas (7.5mm: BAL29; 9mm: BAL40)

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm				
			1800	2400	2440	2725	3000
7.5	10.9	900			✓	✓	✓
		1200	✓		✓	✓	✓
9	13	1200		✓			✓



7.5mm & 9mm Recessed Edge

bgcinnovaldesign.com.au/duratex

Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnovadesign.com.au/duralattice

Duralattice™ is a cellulose fibre reinforced cement sheet. Duralattice™ marries the instant decorative appeal of traditional lattice to the practical durability of fibre cement.

With its easy handling and installation, you'll find Duralattice™ great for use in and around the house and garden. (To comply with codes and regulations when working with balustrades, always ask a structural engineer for design specs.)

- / Especially good for gazebos, pergolas, privacy screens, verandah enclosures, fencing, gable infills and trellises
- / Use also for poolside and other shade-providing structures
- / Made as single unit without joints
- / Feature panels and many more fashionable and practical applications

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm	
			1800	2400
6	7	900	✓	✓
		1200	✓	✓



bgcinnovadesign.com.au/duralattice
Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnoovadesign.com.au/duraliner-plus

Duraliner™ Plus is a general-purpose fibre cement building board. Designed for flush jointing, Duraliner™ Plus is highly effective for use in wet areas, interior linings, ceilings, as a substrate for ceramic wall tiles and for fire and acoustically-rated interior walls.

You can also specify Duraliner™ Plus for soffits and other external applications where there'll be no direct impact from the weather.

- / Wide range of applications
- / Specify as part of fire and acoustic-rated wall systems
- / Rebated on 3 edges for easy jointing and installation

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm					
			1800	2400	2700	3000	3600	4200
6	8.9	900		✓		✓		
		1200	✓	✓	✓	✓	✓	✓
		1350		✓		✓	✓	✓
9	13.2	1200		✓	✓	✓	✓	
		1350				✓	✓	
12	17.9	1200				✓		



6mm, 9mm & 12mm Recessed Edge

bgcinnoovadesign.com.au/duraliner-plus

Some sizes may not be available in all states, please check with your local BGC office for availability.




bgcinnoovadesign.com.au/duralux-plus

Duralux™ Plus is a general-purpose fibre cement building board that you can use for many different and demanding applications. Among these are interior lining, domestic and commercial soffits, exposed beam ceilings, in wet areas and as a substrate for ceramic wall tiles.

Quick and easy to apply to timber or steel, its three available thicknesses make Duralux™ Plus a flawless choice for many domestic and commercial applications.

- / Easy, correct installation and maintenance will ensure full water-resistance
- / Simply decorated in a variety of finishes
- / Classified as Type B Category 2 product for use in applications sheltered from direct weathering

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm			
			2400	2700	3000	3600
4.5*	6.8	900	✓		✓	
		1200	✓	✓	✓	✓
6	8.9	900			✓	
		1200	✓	✓	✓	✓
9	13.2	1200	✓	✓	✓	



bgcinnoovadesign.com.au/duralux-plus
*Available in QLD only



bgcinnovaldesign.com.au/compressed

High-density Compressed fibre cement sheeting is a superlative substrate for interior floors in framed-construction wet areas. Ideal for upper storeys and transportable buildings, it's equally suited for use as a substrate for exterior decks.

Compressed fibre cement sheeting is manufactured from cement, finely-ground silica, cellulose fibres and water. After forming, we compress the sheeting to high density, then cure it in a high-pressure steam autoclave for an exceptionally durable, fit-for-purpose product.

- / Immune to permanent water damage
- / Impact-resistant and immune to termite attacks
- / Highly durable and dimensionally stable
- / Suitable for wet areas and for cladding external decking
- / Non-combustible and easy to work

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm					
			1500	1800	2100	2400	2700	3000
15	26	900	✓	✓	✓	✓	✓	✓
		1200	✓	✓	✓	✓	✓	✓
18	31.1	900	✓	✓		✓		✓
		1200	✓	✓	✓	✓		✓
24	41.2	1200				✓		

bgcinnovaldesign.com.au/compressed

Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnovadesign.com.au/ctu

Ceramic Tile Floor Underlay is a specially-formulated fibre cement sheet. It's designed as a stable substrate for slate and ceramic floor tiles, so you can install ceramic tile floor underlay over new or existing timber floorboards, plywood or particleboard flooring.

In dry areas, apply tiles directly to Ceramic Tile Floor Underlay for an impervious, easily-cleaned surface. In wet areas and anywhere subject to accidental flooding or watersplash, install a waterproof membrane between the underlay and your tiling.

- / Specially-manufactured fibre cement sheet
- / Excellent substrate for floor tiles, both slate and ceramic
- / For dry and wet areas (see above)
- / Can be applied to both new and existing timber floorboards, plywood or particleboard

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm
			1800
6	8.8	900	✓
		1200	✓



bgcinnovadesign.com.au/ctu
Some sizes may not be available in all states, please check with your local BGC office for availability.



bgcinnovadesign.com.au/vcu

We've designed, tested and manufactured Vinyl & Cork Underlay sheets to deliver a smooth, durable surface for your vinyl and cork tiles. You can also use the sheets under parquetry floor tiles, and they're water-resistant and totally proofed against termites and rodents.

Why not cut Vinyl & Cork Tile Floor Underlay sheets to size onsite. Ideally you should use a 180mm Durablade, remembering always to use dust-collection devices, an approved dust mask and safety glasses.

- / Completely termite and rodent proof
- / Immune to water damage
- / Non-swelling
- / Can also be used under parquetry floor tiles
- / Complies with AS2908.2 – Cellulose Cement Products - Part 2 Flat Sheets

THICKNESS mm	WEIGHT kg/m ²	WIDTH mm	LENGTH mm
			1200
5	7.5	900	✓



bgcinnovadesign.com.au/vcu

Some sizes may not be available in all states, please check with your local BGC office for availability.

Warranty

We warrant that our products are free from defects caused by faulty manufacture or materials for a period of 15 years from the date of purchase. If you acquire any defective products, we will repair or replace them, supply equivalent replacement products or refund the purchase price within 30 days of receiving a valid claim subject to product inspection and confirmation of the existence of a defect by BGC. We will bear the cost of any such repair, replacement or refund.

THIS WARRANTY IS GIVEN BY:

BGC FIBRE CEMENT PTY LTD
121 Bannister Rd Canning Vale WA 6155
Phone 08 9334 4900 Fax 08 9334 4749

To claim under this warranty, you must provide proof of purchase as a consumer and make a written claim (including any costs of claiming) to us at the address specified within 30 days after the defect was reasonably apparent, or if the defect was reasonably apparent prior to installation, the claim must be made prior to installation. You may not claim under this warranty for loss or damage caused by:

- / Faulty or incorrect installation by non-BGC installers (BGC's installation procedures are at www.bgcinnovadesign.com.au).
- / Failure to comply with the National Construction Code (NCC) or any applicable legislation, regulations approvals and standards.
- / Products not made or supplied by BGC.
- / Abnormal use of the product.
- / Normal wear and tear.

The benefits available under this warranty are in addition to other rights and remedies of the consumer under the law. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

Terms and Conditions

BGC Fibre Cement's Terms and Conditions of Sale ("Agreement"), as in place and published at the date of this brochure, which are available upon request or on our website at www.bgcinnovadesign.com.au. The purchaser's terms and conditions, howsoever provided, do not form part of the Agreement.

Notes

A series of horizontal dashed lines for taking notes.

To contact
your nearest
BGC stockist,
Please call:

ADELAIDE

71 FROST ROAD
SALISBURY SOUTH
SOUTH AUSTRALIA 5106
TELEPHONE 08 8250 4962
FACSIMILE 08 8258 2612

BRISBANE

53 ARGON STREET
CAROLE PARK
QUEENSLAND 4300
TELEPHONE 07 3183 8100
FACSIMILE 07 3271 1733

MELBOURNE

200 MAIDSTONE STREET
ALTONA VICTORIA 3018
TELEPHONE 03 9392 9444
FACSIMILE 03 9392 9404

PERTH

121 BANNISTER ROAD
CANNING VALE
WESTERN AUSTRALIA 6155
TELEPHONE 08 9334 4900
FACSIMILE 08 9334 4749

SYDNEY

233 MILPERRA ROAD
BANKSTOWN
NEW SOUTH WALES 2200
TELEPHONE 02 9709 0600
FACSIMILE 02 9771 9870

TECHNICAL HELP LINE

1300 652 242

BGCINNOVADESIGN.COM.AU



Quality
ISO 9001
SA 8000