MATCH THE PRODUCT CO	LOURS ON THI	S FLYER TO TH	HE PRODUC	PACKAGI	GING ON TI	HE SHELF	Included FeatureOptional Extra	oors	Doors	Doors	oors	ed track	ed track	track		ling	ng	de			
Product / System	System Type	Max. Door / leaf weight	Max. Door / leaf width (mm)	Door Thickness (mm)	Door Opening (mm)	Suits No. Of doors	Track Type	Internal Do	Wardrobe [Cupboard I	Cabinet Do	Wall mounted	Top mounted	Floor fixed	Top hung	Bottom rolling	End pivotting	Bottom guide		End stop	Pelmet
ROBEMAKER	Sliding	40kg per door	Up to 820	30 - 40	2440	2 to 3	Alum White, Birch & Anodised		•	•				•							
QUICK FIX	Sliding	25kg per door	Up to 1220	19 - 32	2400	2 to 3	Aluminium - double "J" Mill finish		•	•			•					•			
QUAD BALL	Sliding	40kg per door	Up to 920	25 - 50	760-920	1	Aluminium - open "J" Mill finish	•				•									
BARRACUDA BIFOLD	Bi-Folding	13kg per leaf	Up to 450	19 - 35	915	2 leaf	Aluminium - enclosed Mill finish	•	•				•				•		•		
CABINETMAKER	Sliding	20kg per door	Up to 915	15 - 18	1800	3	Aluminium - White			•	•			•							
TROJAN	Sliding	120kg per door	Up to 1500	28	1500	1	Aluminium - enclosed Anodised	•					•					•		•	
TRIUMPH FOLDING	Multi-Folding	25kg per leaf	Up to 915	25 - 35	1830	4 leaf	Aluminium - enclosed Anodised	•					•				•		•		
TRIUMPH SLIDING	Sliding	68kg per door	Up to 915	22 - 35	915	1	Aluminium - enclosed Anodised	•				•	•							•	
CENTURION (Heavy Duty Arrow)	Sliding	60kg per door	Up to 915	30 - 50	915	1	Galvanised steel - open "J"	•				•								•	
ARROW	Sliding	30kg per door	Up to 915	25 - 50	915	1	Galvanised steel - open "J"	•				•			•			•		•	
FORERUNNER	Sliding	50kg per door	Up to 915	22 - 35	915	1	Aluminium - enclosed Mill finish	•				•	•		•			•		•	
FORERUNNER PELMET	Sliding	50kg per door	Up to 915	22 - 35	915	1	Aluminium - enclosed White	•				•			•					•	•
PLASTIC TRACK	Sliding	6kg per door	Up to 950	5	1800	2	Plastic - Brown or White			•	•			•							







1800 COWDROY www.cowdroy.com.au

DOOR TRACK SELECTION GUIDE

Cupboard

The following points should help you select the appropriate door track system for your needs.

Door mounted:	Door width:					
Wall or Top mounted:	Door thickness:	Number of doors:				

Will your track be wall mounted or top mounted? Be aware of available fixing points/studs and any obstructions before committing to a fixing type.

Is your doorway a high traffic area subject to constant use? Upgrading to an enclosed track or a heavier system can greatly increase the operating life of your door track.

Want to keep the noise to a minimum - kids bedroom, ensuite? Enclosed aluminium tracks are far less noisy than open steel tracks and often run much more smoothly.

Is humidity or dust a concern in your door location? Enclosed tracks offer a greater resistance to the build up of dirt and dust, thus increasing the operating life of your door track.

Do you simply want a track that looks good? Enclosed tracks are much more appealing and may be painted to suit decor, or you may prefer a pelmeted wall fix track.

ARROW Sliding Internal Door 30kg

- Single internal doors Wall fix application
- Hollow core doors

Folding

- Door widths up to 915mm
- 25mm min. door thickness

FORERUNNER PELMET **Sliding Internal Doors** 50kg

Single internal doors

Wall fix applications

· Hollow & solid core doors

Door widths up to 1220mm


22mm min, door thickness



Cabinet




BARRACUDA





40kg





CENTURION

