

WALNUT





TEAK



SLATE GREY



IRONBARK

DECKING—FASCIA—SCREENING

CO-EXTRUDED DECKING - 25 YEAR WARRANTY



Walnut/Teak
142mm x 22mm x 5400mm



Ironbark/Ghostgum
142mm x 22mm x 5400mm



Graphite/Maple 142mm x 22mm x 5400mm

FASCIA/SCREENING



Maple, Graphite, Walnut, Teak, Ghostgum, Iron Bark. 71mm x 10mm - Available in 1800, 2700 & 5400mm lengths



Co-extruded decking is the latest innovation to hit the market. Advanced technology creating a protective outer shield layer .

Low maintenance, easy to clean & highly fade resistant.

Six colours to choose from. Dual coloured boards with matching Fascia/Screen

Featuring the warmth and natural look of timber, composite decking boards are designed to perform in both residential and commercial applications. Featuring slip resistance, low maintenance and the guarantee that the product will not rot or splinter. Made to withstand the harsh Australian weather conditions.

Our composite decking products are crafted with a concealed clip system that will hide ugly screw and nail heads. Perfect for pool surroundings, decks, patios, terraces, balconies and rooftop gardens. Available in a large range of colours in both hollow and solid profiles.

No matter your requirements, we can provide you with a reliable and durable composite decking that lasts.

WPC DECKING - 15 YEAR WARRANTY



135mm x 23mm x 5400mm



Mocha Solid 135mm x 23mm x 5400mm

FASCIA/SCREENING



Slate Grey Solid 135mm x 23mm x 5400mm





96mm x 12mm - Available in 1800, 2700 & 5400mm lengths





Cocoa Hollow 135mm x 25mm x 5400mm



Mocha Hollow 150mm x 25mm x 5400mm



Slate Grey Hollow 150mm x 25mm x 5400mm

- * Termite resistant
- * No Oiling Required
- * Made using eco-friendly materials
- * Will not crack, rot or splinter
- * Slip Resistant
- * No algae growth

- * Invisible fixing
- * Easy installation
- * 100% Recycled product
- * Low Maintenance
- * UV stable
- * 15 Year Warranty

EASY INSTALLATION

Starter Board



The first board laid on your new deck is referred to as a starter board. Boards are fastened with starter clips.

The Starter clip allows you to accommodate the required 10mm distance from the wall/structure.

Hidden Fixing



Our boards are designed to be used with our ABS plastic hidden clipping system.

The clips will guarantee a consistent 5mm gap between the edges of the boards.

Fascia



Our fascia is an ideal way of finishing the edges of your new deck.

Pre drilling of the fascia is required prior to fastening.

Fascia is available in matching deck colours

Breaker Board



The breaker board method of joining is recommended on long spans instead of butt joining. Using a breaker board will allow for additional board movement.

Double Joists



When joining boards using a Butt join, a double joist is required.

Each joist requires a fitting.

Gapping Requirements

Between Boards - Side by Side. - 5mm Board End to Solid Structure. - 10mm Against Wall - Parallel. - 10mm End to End Butt Join - Cold Day. - 7mm End to End Butt Join - Hot Day. - 5mm Butt Join to Breaker Board. - 5mm

Maximum Joist Distance

Hollow Profile boards

- 350mm Centres for Domestic.

Solid Profile boards

- 450mm Centres for Domestic.
- 400mm Centres for Commercial

Co-Extruded boards

- 400mm Centres for Domestic.

Accessories



Joining Clip



Starter Clip



Breaker Board Clip



NSW - TAS - VIC - SA - WA - ACT - NT - QLD